

Gottlieb	Williams	Bally	Pouces	Millimètres
	23A-6300	R-243	5/16 (post)	7.9375
	23A-6311	R-402	5/16 (post)	
14793			23/64 (OD)	9.128 (7)
10217			3/8	9.525 (10)
15705			27/64 (OD)	10.715 (8)
17493			7/16	11.1125
		R-392	15/32	11.9
10218	23A-6301/-R		3/4	19.05
10219	23A-6302	R-135	1	25.4 (25)
13149 (petit flipper)		R-111-9 (flipper)	1	
	23A-6303		1-1/4	31.75 (30)
13151 (flipper)	23A-6505		1-1/2	
10220	23A-6304	R-141	1-1/2	38.1 (40)
10221	23A-6305	R-196	2	50.8 (50)
	23A-6306 (1970)		2-5/16	58.7375 (60)
	23A-6306 (1977)		2-3/8	60.325 (60)
10222		R-284-5	2-1/2	63.5 (65)
	23A-6307		2-7/8	73.025 (70/75)
10223		R-295-5	3	76.2 (75)
	23A-6308		3-3/8	85.725 (85)
10224		R-296-5	3-1/2	88.9 (90)
	23A-6309		3-7/8	98.425 (100)
10225		R-385-5	4	101.6 (100)
	23A-6530 (1977)		4-1/2	114.3 (115)
10226	23A-6310		5	127 (125)
	23A-6429 (1977)		6	152.4 (150)
	23A-6327		Lance-bille	Lance-bille